

(R)

Premium ANTI SCRATCH Collection 2024 - 2025 EDITION



NEXT GENERATION
SOFT TOUCH CORE LAMINATES







Super Matt - Soft Touch

PURE WHITE	OM-500-BW	WHITE	OM-501-BW	OFF WHITE	OM-502-BW
CREAM	OM-516-BR	LIGHT BEIGE	OM-512-BR	SOFT WHEAT	OM-517-BR
CLAY	OM-513-BR	DUSK MOSS BROWN	OM-515-BR	LATTE	OM-506-GR

GENERAL USE & CARE GUIDE:

Rafahia Laminates are easy to maintain. Our laminates will last for years with proper use and appropriate care,

- 1. To remove stubborn stains use mild household glass cleaners such as Colin. Wipe the surface gently with a non-abrasive cloth.
- 2. Avoid using abrasive liquid cleaners, bleaches or solvents as they can damage the laminate surface. Cleaning should be done with water and a clean, non-abrasive cloth.
- 3. Do not use thinner on the surface of the Operando Laminates.



Super Matt - Soft Touch



Premium Anti Scratch Collection

Rafahia Super Matt

ADVANCE FEATURES

























Polymer Laminate

High Heat Resistance

Chemical Resistance

Termite Free

Anti-Bacterial Properties









Easy to Clean

Compatible Working High Impact Resistance with Plywood & MDF

No Edge Banding Strip Required

Why Polymer Laminates are the Best Choice compare to other laminates?

Parameters	PVC	PET-G	ASA	ACRYLIC	POLY
Best Quality + Cost E ff ective	NO	NO	NO	NO	YES
Eco Friendly	NO	NO	YES	NO	YES
Soft Touch Matt Life	Short	Short	Medium	Medium	Long
Durable	2-3 months	1 year	1 year	2 years	10 years
Rigid / Flexible	Rigid	Rigid	Rigid	Rigid	Flexible
Bendable	O°	O°	O°	O°	180°
Weight	Heavy	Heavy	Medium	Medium	Light
UV / Anti-Yellow	Low	Low	Medium	Medium	High
Weather Resistance	Bad	Good	Good	Good	Excellent
Heat Resistance	Bad	Good	Good	Good	Excellent

INSTALLATION INSTRUCTIONS::

- 1. Before use, stir the POLYBOND adhesive and do not mix water.
- 2. Clean the dust particles from the surface of the substrate (Plywood, MDF, Chipboard) with a clothe, soft brush sponge or sandpaper.
- 3. Apply the adhesive even with a brush, roller or adhesive spray on both the laminate and the substrate. (Plywood, MDF, Chipboard).
- 4. When pressing on the laminate base(Plywood, MDF, Chipboard), use a soft pressure roller or a normal pressing technique. Pressing must be done from the panel and moved to the side line and corners of the panel.
- 5. Make sure the laminate is sufficiently pressed for almost 24-30 hours to reach full bond strength.



Welcome to Operando Laminates - The Leading Polymer Laminate Manufacturing Company

We take immense pride in crafting exceptional Laminates that redefine spaces and elevate interior aesthetics. Operando Laminates leads the way in revolutionizing surface solutions with innovative products. With a strong focus on creativity and innovation, we are committed to delivering customer-friendly products that exceed expectations. Experience the Operando Laminates difference – where quality is our passion and customer satisfaction is our utmost priority. Explore our range of exceptional products and discover the perfect solution for your needs.

SPARK YOUR IMAGINATION

Quality | Reliability | Consistency

Our Products:

2024 Premium ANTI SCRATCH Collection









@operandolaminates



sales@operandolaminates.com

WWW.OPERANDOLAMINATES.COM

